



# NovoConnect

NC-X700  
NC-X900

## 4K Video Conference System Solutions

The NovoConnect NC-X700 and NC-X900 are ultra-high-quality 4K smart conference solutions that support the cross-platform connection of conference projection display equipment via Wi-Fi or Ethernet. With built-in smart wireless collaboration and seamlessly switch to a digital signage, these solutions can be used to conduct screen sharing for smart collaboration during conferences, and they can also be used to broadcast digital messages before or after any meetings.

These solutions are suitable for medium and small conference rooms, offices, open office spaces, lobby areas, small studios, and reception rooms.



(optional)





## Key Features

### Wireless Presentation



- Ultra HD 4K ultra-high-quality resolution.
- Supports cross-platform systems (Windows 10, macOS, Ubuntu, Android, iOS, and ChromeOS)
- Native screen mirroring, supports Windows 10 Miracast<sup>®</sup>, AirPlay<sup>®</sup>, and Google Cast.
- Supports NovoConnect Software/App.
- Instantly connect via a web browser to mirror your laptop screen.

\* For more information, please visit <http://LaunchNovo.com>



### Wireless Collaboration



- Supports 64 simultaneous participants over a wireless connection, instant file-sharing, and interactive annotation.
- Supports AES-256 data encryption, offering the highest level of information security.





## Supports dual wireless network modules (the NC-X900 only)

The dual wireless network design allows simultaneous independent projection for Windows 10 Miracast and for connecting to Wi-Fi or sharing a wireless hotspot, providing secure and convenient connectivity.

Windows 10 Miracast




Wireless hotspot/  
WiFi network



## Dual video output and HDMI input (the NC-X900 only)



- HDMI-Out v2.0 supports 4K (3,840×2,160) ultra-high resolution and 1080P via USB-C. It can connect to two projectors or monitors simultaneously.
- HDMI-In supports connection to video conference systems or HDMI output equipment, ensuring simultaneous video conferences and image sharing.



## Bring Your Own Meeting (BYOM)



- BYOM is designed to bring easy collaboration and communication to any hybrid meeting or lecture.
- Works with popular video conferencing software, including Microsoft Teams, Zoom, Google Meet, Skype, and Webex, making it convenient for remote meetings and teaching.
- Supports USB video conference cameras.



## Digital Signage Player



- Built-in NovoDS Digital Signage System transforms Novo into a signage board.
- Design, publish, and manage: create digital signage in 3 simple steps.
- Simultaneously playback of four 1080P videos (NC-X900 only) or two 4K videos.
- Optional NovoDS Cloud gives signage playlist access and control via a web interface, from your computer or mobile device.



\* For more information please visit <http://novods.com>

# Specifications

Model Name		NC-X700	NC-X900		
System	Operating System	Android™ v7.1			
	CPU	6-core ARM			
	Storage	16GB			
	Display Resolution	HDMI	4K Ultra-HD (3840 x 2160)@30/50/60Hz 1080p (1920 x 1080)@50/60Hz 720p (1280 x 720)@50/60Hz		
		USB-C	1080P		
Features	OS Supported	Windows 10 & 11 (32 bit/ 64bit) macOS 10.7 + Ubuntu 18.04+ iOS 12.1 + Android 5.0 + Chromebook			
	Native Screen Mirroring	AirPlay   Google Cast   Miracast (Windows 10 & 11)			
	Max. Connections	64 Devices			
	Simultaneous Display	4 Screens			
	BYOM	Supported (Connected to in-room USB camera/speakers/microphone)			
	Collaboration (NovoConnect App)	Desktop extension for Windows 10 & 11 Streaming of YouTube and Local Videos Interactive Annotation (AirNote) Moderator, Voting/Polling, File Sharing			
	Digital Signage (NovoDS)	Video	MP4, H.264, VC-1(WMV), MOV, 3GP		
		Audio	MP3, WMA, AAC		
		Image	JPEG, JPG, PNG, BMP		
		Others	PDF, HTML5 (online/offline), Microsoft PowerPoint Twitter, Facebook, Instagram, RSS, Weather, Content update via FTP, Samba, Dropbox, GoogleDrive, OneDrive, and USB drive Free Windows/MacOS software: NovoDS Studio Cloud Service: <a href="https://www.NovoDS.com">https://www.NovoDS.com</a>		
	NT Live (Display Synchronization)	NT LiveReceiver (receiver)	NT LiveReceiver (receiver) NT LiveScreen (sender) Up to 1 to 7 (via Ethernet)		
	Device Management	Remote Manager (Windows) RESTful API (for system integration)			
Security	AES-256 encryption PIN code protection Kensington® lock				
Connectivity	Input	Display	-	HDMI v1.4	
		Audio	-	Line-In 3.5mm mini jack	
	Output	Display	HDMI v2.0 (ARC, HDCP v2.2) (4K@60fps)	HDMI v2.0 (ARC, HDCP v2.2) (4K@60fps) USB-C (1080P@30fps)	
		Audio	Audio-Out (3.5mm Headphone Jack)		
	WiFi	Single WiFi module (2.4GHz/5GHz) IEEE 802.11 b/g/n/ac	Dual WiFi module (2.4GHz/5GHz) IEEE 802.11 b/g/n/ac		
	Ethernet	LAN 10/100/1000M (RJ45)			
	Power-over-Ethernet (PoE)	-	Yes		
	RS232	3.5mm headphone Jack (for serial communication)			
USB	USB 2.0 (x1), USB-C (x1)				
Power	Power Supply	AC-DC Adaptor: 5V @ 3A			
General	Dimension (LxWxH)	152mm x 118mm x 24.7mm (5.9' x 4.6' x 0.9')	96mm x 140mm x 28.9mm (7.7' x 5.5' x 1.1')		
	Weight (net)	296g (10.4oz)	446g (15.7oz)		
Accessories	Standard	2x WiFi Antennas   HDMI Cable   USB Cable   Remote Control Power Adapter   Wall Mount Kit Document Kit			
	Optional	LauncherPlus (Availability varies depending on country.)			



[www.vivitekcorp.com](http://www.vivitekcorp.com)

© 2021 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.

A brand of DELTA